

Deleting a User

You can add a user with the **deleteUser** method.

Permission to run the request: Account Owner, Administrator, Organization Administrator.

Parameters

Parameter	Type	Description
credentials (required)	credentials	Read the description of the Credentials object.
userId (required)	string	ID of the user you want to delete.

Return Value

When a call is processed successfully, the system returns an object with the following properties:

Parameter	Type	Description
success	bool	True if the user has been deleted

Possible Errors

Error	Description
Unknown user	The user with the given ID cannot be found.
Permission Denied	You have no permissions to delete the specified user

Sample Call

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns="http://ispringlearn.com/go/services/api/soap">
  <SOAP-ENV:Body>
    <DeleteUserRequest>
      <credentials>
        <accountUrl>http://myaccount.ispringlearn.com</accountUrl>
        <email>email@email.com</email>
        <password>password</password>
      </credentials>
      <userId>1</userId>
    </DeleteUserRequest>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

Sample Response

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns="http://ispringlearn.com/go/services/api/soap">
  <SOAP-ENV:Body>
    <DeleteUserResult>
      <success>true</success>
    </DeleteUserResult>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```