

Changing User Portal Settings

You can change the user portal settings with the **setUserPortalSettings** method.

Permission to run the request: Account Owner, Administrator.

Parameters

Parameter	Type	Description
credentials (required)	credentials	Read the description of the Credentials object.
userPortalEnabled (required)	bool	True if you want to enable the user portal in your account.
welcomeTitle (optional)	string	Welcome text to be displayed in the user portal.
instructionMessage (optional)	string	Text of the introduction message to be displayed in the user portal.
showHistoryReports (optional, default:true)	bool	True if you want to show the History tab that logs all user's activities.
coursesSortColumn	string	Specify how courses are sorted in the user portal: by status, title or duration.

Return Value

After the request has been completed, the system returns an object with the following properties:

Parameter	Type	Description
success	bool	True if the settings have been changed.

Possible Errors

Text	Description
Permission denied	You have no permissions to get the settings of the user portal. Only the account owner and the administrator have permissions to send the request.
Wrong parameters	The system failed to process the request because it did not contain all necessary parameters.

Sample Call

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns="http://ispringlearn.com/go/services/api/soap">
  <SOAP-ENV:Body>
    <SetUserPortalSettingsRequest>
      <credentials>
        <accountUrl>http://myaccount.ispringlearn.com</accountUrl>
        <email>email@email.com</email>
        <password>password</password>
      </credentials>
      <userPortalEnabled>true</userPortalEnabled>
      <welcomeTitle>Welcome title</welcomeTitle>
      <instructionMessage>Instruction message</instructionMessage>
      <showHistoryReports>true</showHistoryReports>
      <coursesSortColumn>status</coursesSortColumn>
    </SetUserPortalSettingsRequest>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

Sample Response

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns="http://ispringlearn.com/go/services/api/soap">
  <SOAP-ENV:Body>
    <SetUserPortalSettingsResult>
      <success>true</success>
    </SetUserPortalSettingsResult>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```