

Inviting Users to View Content Item

You can invite a user to view a content item with the `inviteUsersToContentItem` method.

Permission to run the request: Account Owner, Administrator, Organization Administrator, Publisher.

Parameters

Parameter	Type	Description
credentials (required)	credentials	Read the description of the Credentials object.
contentItemId (required)	string	ID of the content item you want to invite users to.
users (optional)	string[]	Array of IDs of the users who will be invited to view the content item.
groups (optional)	string[]	Array of group IDs which members will be invited to view the content item.
emails (optional)	string[]	Array of email addresses to send invitations to (available for public content only).
invitationMessage(optional)	string	Invitation text added to the e-mail.
autoAddPermissions(optional, default: true)	bool	If true and a user/group has no permissions to view the given content item, these permissions will be added automatically.

Return Value

After the request has been completed, the system returns an object with the following properties:

Parameter	Type	Description
success	bool	True if the invitations have been sent successfully.
usersWithoutPermission	string[]	An array of user IDs who have no permissions to view the given content item.
groupsWithoutPermission	string[]	An array of group IDs which members have no permissions to view the given content item.

Sample Call

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns="http://ispringlearn.com/go/services/api/soap">
  <SOAP-ENV:Body>
    <InviteUsersToContentItemRequest>
      <credentials>
        <accountUrl>http://myaccount.ispringlearn.com</accountUrl>
        <email>email@email.com</email>
        <password>password</password>
      </credentials>
      <contentItemId>1234</contentItemId>
      <users>
        <id>1</id>
        <id>2</id>
      </users>
      <groups>
        <id>1</id>
        <id>2</id>
      </groups>
      <emails>
        <email>user1@email.com</email>
        <email>user2@email.com</email>
      </emails>
      <invitationMessage>Invitation Message</invitationMessage>
    </InviteUsersToContentItemRequest>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

Sample Response

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns="http://ispringlearn.com/go/services/api/soap">
  <SOAP-ENV:Body>
    <InviteUsersToContentItemResult>
      <success>true</success>
    </InviteUsersToContentItemResult>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```