

Deleting a User

Method: **deleteUser**

Permissions to Run the Request

Account Owner, Account Administrators, Department Administrators, or [custom roles](#).

Department Administrators and users with a custom role can delete users belonging to the departments they manage and their sub-departments.

Parameters

Parameter	Type	Description
credentials (required)	credentials	Read the description of the Credentials object.
userId (required)	string	The ID of the user you want to delete.

Return Value

When a request is processed successfully, the system returns an object with the following properties:

Parameter	Type	Description
success	bool	True if the user has been deleted

Possible Errors

Error	Description
Unknown user	The user with the given ID cannot be found.
Permission Denied	No permissions to delete the specified user

Sample Call

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns="http://ispringlearn.com/go/services/api/soap">
  <SOAP-ENV:Body>
    <DeleteUserRequest>
      <credentials>
        <accountUrl>http://myaccount.ispringlearn.com</accountUrl>
        <email>email@email.com</email>
        <password>password</password>
      </credentials>
      <userId>string</userId>
    </DeleteUserRequest>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

Sample Response

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns="http://ispringlearn.com/go/services/api/soap">
  <SOAP-ENV:Body>
    <DeleteUserResult>
      <success>true</success>
    </DeleteUserResult>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```