

# Inviting Users to View Content Item

You can invite a user to view a content item with the `inviteUsersToContentItem` method.

Permission to run the request: Account Owner, Administrator, Organization Administrator, Publisher.

## Parameters

Parameter	Type	Description
credentials (required)	credentials	Read the description of the <a href="#">Credentials</a> object.
contentItemId (required)	string	ID of the content item you want to invite users to.
users (optional)	string[]	Array of IDs of the users who will be invited to view the content item.
groups (optional)	string[]	Array of group IDs which members will be invited to view the content item.
emails (optional)	string[]	Array of email addresses to send invitations to (available for public content only).
invitationMessage(optional)	string	Invitation text added to the e-mail.
autoAddPermissions(optional, default: true)	bool	If true and a user/group has no permissions to view the given content item, these permissions will be added automatically.

## Return Value

After the request has been completed, the system returns an object with the following properties:

Parameter	Type	Description
success	bool	True if the invitations have been sent successfully.
usersWithoutPermission	string[]	An array of user IDs who have no permissions to view the given content item.
groupsWithoutPermission	string[]	An array of group IDs which members have no permissions to view the given content item.

## Sample Call

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns="http://ispringlearn.com/go/services/api/soap">
  <SOAP-ENV:Body>
    <InviteUsersToContentItemRequest>
      <credentials>
        <accountUrl>http://myaccount.ispringlearn.com</accountUrl>
        <email>email@email.com</email>
        <password>password</password>
      </credentials>
      <contentItemId>1234</contentItemId>
      <users>
        <id>1</id>
        <id>2</id>
      </users>
      <groups>
        <id>1</id>
        <id>2</id>
      </groups>
      <emails>
        <email>user1@email.com</email>
        <email>user2@email.com</email>
      </emails>
      <invitationMessage>Invitation Message</invitationMessage>
    </InviteUsersToContentItemRequest>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

## Sample Response

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns="http://ispringlearn.com/go/services/api/soap">
  <SOAP-ENV:Body>
    <InviteUsersToContentItemResult>
      <success>true</success>
    </InviteUsersToContentItemResult>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```