

# Deleting a User

Request: **DELETE /user/{user\_id}**

## Permissions to Run the Request

*Account Owner, Account Administrators, Department Administrators, or [custom roles](#).*

*Department Administrators and users with a custom role can delete users belonging to the departments they manage and their sub-departments.*

## Request Headers

Parameter	Description
X-Auth-Account-Url (required)	The base URL of the account, e.g. <a href="http://myaccount.ispringlearn.com">http://myaccount.ispringlearn.com</a>
X-Auth-Email (required)	The <b>login</b> of <i>Account Owner, Account Administrator, Department Administrator</i> , or a user with <a href="#">a custom role</a> .
X-Auth-Password (required)	The password of <i>Account Owner, Account Administrator, Department Administrator</i> , or a user with <a href="#">a custom role</a> .

## Possible Response Codes

Code	Text	Description
204	Successful operation	A user is deleted.
400	Bad Request	A request error.
401	Unauthorized	Authorization error.
403	Permission Denied	The user doesn't have enough permissions to delete another users.

## Sample Request

```
DELETE /user/f29d887c-5cff-11e9-9e6a-0a580af40692 HTTP/1.1
Host: api-learn.ispringlearn.com
X-Auth-Account-Url: https://myaccount.ispringlearn.com
X-Auth-Email: email@email.com
X-Auth-Password: password
```

## Sample Response

```
HTTP/1.1 204 Successful operation
Connection: close
```