

Getting a List of Groups

Method: **getGroups**

Permissions to Run the Request

Account Owner, Account Administrators, Department Administrators, or [custom roles](#).

Parameters

Parameter	Type	Description
credentials (required)	credentials	Read the description of the Credentials object.

Return Value

After the request has been completed, the system returns an object with the following properties:

Parameter	Type	Description
group	array	An array containing the following values: 'groupId', 'name'.

Sample Request

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="https://schemas.xmlsoap.org/soap/envelope/"
  xmlns="https://ispringlearn.com/go/services/api/soap">
  <SOAP-ENV:Body>
    <GetGroupsRequest>
      <credentials>
        <accountUrl>https://myaccount.ispringlearn.com</accountUrl>
        <email>email@email.com</email>
        <password>password</password>
      </credentials>
    </GetGroupsRequest>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

Sample Response

```
<SOAP-ENV:Envelope xmlns:SOAP-ENV="https://schemas.xmlsoap.org/soap/envelope/"
  xmlns="https://ispringlearn.com/go/services/api/soap">
  <SOAP-ENV:Body>
    <GetGroupsResult>
      <group>
        <groupId>e7fa2c2a-5c39-11e9-a000-0e1426fbe81a</groupId>
        <name>Sales Department</name>
      </group>
      <group>
        ...
      </group>
    </GetGroupsResult>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```