

Activating and Blocking a User

AVAILABLE WITH BUSINESS SUBSCRIPTION

Request: **POST** /user/{user_id}/status

Permissions to Run the Request

Account Owner, Account Administrators, Department Administrators, or [custom roles](#).

Department Administrators and users with a custom role may activate or deactivate only users belonging to the departments they manage or their daughter departments.

Request Headers

Header	Description
Authorization (required)	Access token. You can obtain a token by making a request
Parameter	Description
user_id (required)	The ID of a user you want to activate or deactivate
status	To block a user, add 3 (<status>3</status>) in the status row. To active a user, type 1 (<status>1</status>)

Possible Response Codes

Code	Text	Description
200	OK	A user's status is changed
400	Bad Request	A request error
401	Unauthorized	An authorization error
403	Permission Denied	The user doesn't have enough permissions to activate or deactivate users. For example, <i>Department Administrators</i> can't activate or deactivate users who don't belong to the departments they manage

Sample Request

```
POST /user/43f4a84c-6280-11e9-8686-a6210366ac32/status https/1.1
Host: api-learn.ispringlearn.com
Authorization: p-1sJDjmULL5DdpXPJTcbm4jVIaWVHvNmrjAxATRbNE
Content-Type:application/xml

<?xml version="1.0" encoding="UTF-8"?>
<request>
  <status>1</status>
</request>
```

Sample Response

```
https/1.1 200 OK
```