

Getting a List of Groups

AVAILABLE WITH BUSINESS SUBSCRIPTION

Method: **getGroups**

Permissions to Run the Request

Account Owner, Account Administrators, Department Administrators, or [custom roles](#).

Parameters

Parameter	Type	Description
token (required)	string	Access token. You can obtain a token by making a request .

After the request has been completed, the system returns an object with the following properties:

Parameter	Type	Description
group	array	An array containing the following values: 'groupId', 'name'.

Sample Request

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="https://schemas.xmlsoap.org/soap/envelope/"
  xmlns="https://ispringlearn.com/go/services/api/soap">
  <SOAP-ENV:Body>
    <GetGroupsRequest>
      <credentials>
        <token>p-1sJDjmULL5DdpXPJTcbm4jVIawVHvNmrjAxATRbNE</token>
      </credentials>
    </GetGroupsRequest>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

Sample Response

```
<SOAP-ENV:Envelope xmlns:SOAP-ENV="https://schemas.xmlsoap.org/soap/envelope/"
  xmlns="https://ispringlearn.com/go/services/api/soap">
  <SOAP-ENV:Body>
    <GetGroupsResult>
      <group>
        <groupId>e7fa2c2a-5c39-11e9-a000-0e1426f8e81a</groupId>
        <name>Sales Department</name>
      </group>
      <group>
        ...
      </group>
    </GetGroupsResult>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```