

Adding a User

You can add a user with the method: **addUser**.

Permission to run the request: Account Owner, Administrator, Organization Administrator.

Parameters

Parameter	Type	Description
credentials (required)	credentials	Read the description of the Credentials object.
email (required)	string	Email of the new user.
login(optional)	string	Login of the new user.
password (optional)	string	Password of the new user. If it's not specified, the password will be generated automatically.
organizationId (optional)	string	Organization ID the user will be added to.
sendLoginEmail (optional, default: true)	bool	Parameter that determines whether an email is sent to the added user.
invitationMessage (optional)	string	Text of an invitation message in the email.
role (optional)	string	Assign a role to the new user: 10 - regular user, 20 - publisher, 30 - organization admin 40 - account admin
groups (optional)	string[]	An array with the IDs of the groups the user will be added to.

Return Value

After the request has been completed, the system returns an object with the following properties:

Parameter	Type	Description
userId	string	ID of the added user.
exceededGroups	string[]	An array of group IDs the user hasn't been added to due to the exceeded user limit.

Possible Errors

Error	Description
User with the same email is already registered.	A user with the specified e-mail address already exists.
User with the same login is already registered.	A user with the specified e-mail address already exists.
Number of user accounts is exceeded	A user hasn't been added because the number of user accounts supported by your subscription plan has been exceeded.
Permission denied	An authorized user does not have enough permissions to handle the operation. For example, an organization admin can't add users to another organization.
Wrong parameters	Some of the sent parameters are incorrect.

Sample Call

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns="http://ispringlearn.com/go/services/api/soap">
  <SOAP-ENV:Body>
    <AddUserRequest>
      <credentials>
        <accountUrl>http://myaccount.ispringlearn.com</accountUrl>
        <email>email@email.com</email>
        <password>password</password>
      </credentials>
      <email>user@email.com</email>
      <password>password</password>
      <sendLoginEmail>true</sendLoginEmail>
      <invitationMessage>Message</invitationMessage>
      <role>20</role>
      <groups>
        <id>1</id>
        <id>2</id>
      </groups>
    </AddUserRequest>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

Sample Response

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns="http://ispringlearn.com/go/services/api/soap">
  <SOAP-ENV:Body>
    <AddUserResult>
      <userId>1</userId>
      <exceededGroups />
    </AddUserResult>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```