

Getting List of Users

You can obtain the list of users with the **getUsers** method.

Permission to run the request: Account Owner, Administrator, Organization Administrator.

Parameters

Parameter	Type	Description
credentials (required)	credentials	Read the description of the Credentials object.
groupId (optional)	string	If specified, this method selects users belonging to a specific group.
organizationId (optional)	int	If specified, this header selects users belonging to a specific organization.

Return Value

After the request has been completed, the system returns an object with the following properties:

Parameter	Type	Description
users	UserProfile[]	Array of user profiles. The UserProfile object has the same properties as the getUserProfile method.

Possible Errors

Error	Description
Permission denied	The user doesn't have enough permissions to handle the request. For example, an organization admin can't request info about users from another organization.

Sample Call

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns="http://ispringlearn.com/go/services/api/soap">
  <SOAP-ENV:Body>
    <GetUsersRequest>
      <credentials>
        <accountUrl>http://myaccount.ispringlearn.com</accountUrl>
        <email>email@email.com</email>
        <password>password</password>
      </credentials>
    </GetUsersRequest>
    <groupId>1</groupId>
    <organizationId>2</organizationId>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

Sample Response

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns="http://ispringlearn.com/go/services/api/soap">
  <SOAP-ENV:Body>
    <GetUsersResult>
      <userProfile>
        <userId>string</userId>
        ...
      </userProfile>
      <userProfile>
        <userId>string</userId>
        ...
      </userProfile>
    </GetUsersResult>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```