

Deleting a Group

You can delete a group with the **deleteGroup** method.

Permission to run the request: Account Owner, Administrator, Organization Administrator.

Parameters

Parameter	Type	Description
credentials (required)	credentials	Read the description of the Credentials object.
groupId (required)	string	ID of the group you want to delete.

Return Value

After the request has been completed, the system returns an object with the following properties:

Parameter	Type	Description
success	bool	'True' if the group has been deleted.

Possible Errors

Error	Description
Unknown group	The group was not found.
Permission denied	You have no permissions to delete the specified group.

Sample Call

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns="http://ispringlearn.com/go/services/api/soap">
  <SOAP-ENV:Body>
    <DeleteGroupRequest>
      <credentials>
        <accountUrl>http://myaccount.ispringlearn.com</accountUrl>
        <email>email@email.com</email>
        <password>password</password>
      </credentials>
      <groupId>1</groupId>
    </DeleteGroupRequest>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

Sample Response

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns="http://ispringlearn.com/go/services/api/soap">
  <SOAP-ENV:Body>
    <DeleteGroupResult>
      <success>true</success>
    </DeleteGroupResult>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```