

Getting Permissions of Content Item

You can get security settings of a content item with the **getContentItemPermissions** method.

Permission to run the request: Account Owner, Administrator, Organization Administrator, Publisher.

Parameters

Parameter	Type	Description
credentials (required)	credentials	Read the description of the Credentials object.
contentItemId (required)	string	ID of a content item you want to get permissions of.

Return Value

After the request has been completed, the system returns an object with the following properties:

Parameter	Type	Description
privacy	string	Content item type (public or private)
users	string[]	An array of user IDs who have permissions to view the given private content item.
groups	string[]	An array of group IDs which members have permissions to view the given private content item.

Sample Call

```
<?xml version="1.0" encoding="utf-8"?>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns="http://ispringlearn.com/go/services/api/soap">
    <SOAP-ENV:Body>
        <GetContentItemPermissionsRequest>
            <credentials>
                <accountUrl>http://myaccount.ispringlearn.com</accountUrl>
                <email>email@email.com</email>
                <password>password</password>
            </credentials>
            <contentItemId>1234</contentItemId>
        </GetContentItemPermissionsRequest>
    </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

Sample Response

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
               xmlns="http://ispringlearn.com/go/services/api/soap">
  <soap:Body>
    <GetContentItemPermissionsResult>
      <privacy>private</privacy>
      <useParentPermissions>false</useParentPermissions>
      <users>
        <id>1</id>
        <id>2</id>
      </users>
      <groups>
        <id>1</id>
        <id>2</id>
      </groups>
    </GetContentItemPermissionsResult>
  </soap:Body>
</soap:Envelope>
```